

rammount.com
1-800-497-7479
sales@rammount.com

GDS® Tough-Dock™ Locking Vehicle Bundle for Samsung Tab A7 Lite 8.7"

Part #: RAM-GDS-101LB2-SAM80CP-V7CU **UPC:** 793442018343 **Patented & Pats. Pend.**

FEATURES

- Bundle includes locking GDS® Tough-Dock™, IntelliSkin® Next Gen for Samsung Tab A7 Lite 8.7", hardwire charger with USB-C connector, low-profile double ball mount with C size (1.5") ball and RAM® Pin-Lock™ Knob, backing plate adapter and cable clamp
- Dock features GDS® Technology™ for charging capabilities; uses USB-C port to connect to power
- RAM® Mounts Compatible™ and compatible with the GDS® Hand-Stand™ Hand Strap and Kickstand attachment
- Backed by a 3-year warranty

PRODUCT INFORMATION	
OVERVIEW	<p>Ideal for transportation and large fleet vehicles, this bundle is all you need to pair with your Samsung Tab A7 Lite 8.7". This bundle includes a locking GDS® Tough-Dock™ , IntelliSkin® Next Gen for Samsung Tab A7 Lite 8.7", hardwire charger with USB Type-C connector, C Size double ball mount paired with the short arm with RAM® Pin-Lock™ 5-Pin Security Knob, backing plate adapter, and cable clamp. This bundle is ELD compliant, providing a turnkey solution for your fleet. Always Protected. Always Connected.®</p>

SPECIFICATIONS	
HARDWARE INCLUDED	Assembly Hardware (2) Dock Keys (1) Knob Key (1) 2.10" x 2.60" Steel Backing Plate (4) #8-32 x 1" Screws (4) #8 Split Lock Washers (4) #8 Flat Washers (1) Cable Clamp (1) Vehicle Hardwire Charger
SOCKET TO SOCKET LENGTH	2.5"
HOLE PATTERN	4-Hole AMPS: 1.181" x 1.496" 3-Hole 120-Degree: 1.812" Diameter
BALL SIZE	C Size (1.5")
MATERIALS	Steel Marine-grade aluminum High strength composite
PACKAGING TYPE	Poly Bag
OUTPUT VOLTAGE	5-9VDC*
INPUT CONNECTOR	Female USB Type-C
INPUT CABLE LENGTH	1.2 Meters including 2 Pole Flat Marine Connector

SPECIFICATIONS	
OUTPUT CABLE LENGTH	150mm
OPERATING TEMPERATURE	-20°C to +70°C
STORAGE TEMPERATURE	-40°C to +85°C
REGULATORY	Over Voltage Protection Short Circuit Protection Reverse Polarity Protection RoHS Compliance WEEE Compliance SAE J-1113-5 Load Dump (Transient Voltage) Moisture Resistant
CERTIFICATIONS	CE Certification E-Mark Certification RCM Certification FCC Certification UL 62368-1 Certificaton
WARRANTY	3 year warranty
WEIGHT	3.6 lb