

rammount.com  
1-800-497-7479  
sales@rammount.com

## GDS® Tough-Dock™ Vehicle Bundle for Samsung Tab A7 Lite 8.7"

Part #: RAM-GDS-101B2-SAM80CP-V7CU   UPC: 793442018350   **Patented & Pats.**

Pend.

### FEATURES

- Bundle includes non-locking GDS® Tough-Dock™, IntelliSkin® Next Gen for Samsung Tab A7 Lite 8.7", hardwire charger with USB-C connector, low-profile double ball mount with C size (1.5") ball, backing plate adapter and cable clamp
- Dock features GDS® Technology™ for charging capabilities; uses USB-C port to connect to power
- RAM® Mounts Compatible™ and compatible with the GDS® Hand-Stand™ Hand Strap and Kickstand attachment
- Backed by a 3-year warranty

## PRODUCT INFORMATION

### OVERVIEW

Ideal for transportation and large fleet vehicles, this bundle is all you need to pair with your Samsung Tab A7 Lite 8.7". This bundle includes a non-locking GDS® Tough-Dock™, IntelliSkin® Next Gen for Samsung Tab A7 Lite 8.7", hardwire charger with USB Type-C connector, C Size double ball mount with short arm, backing plate adapter, and cable clamp. This bundle is ELD compliant, providing a turnkey solution for your fleet. Always Protected. Always Connected.®

SPECIFICATIONS	
<b>HARDWARE INCLUDED</b>	Assembly Hardware (1) 2.10" x 2.60" Steel Backing Plate (4) #8-32 x 1" Screws (4) #8 Split Lock Washers (4) #8 Flat Washers (1) Cable Clamp (1) Vehicle Hardwire Charger
<b>SOCKET TO SOCKET LENGTH</b>	2.5"
<b>HOLE PATTERN</b>	4-Hole AMPS: 1.181" x 1.496" 3-Hole 120-Degree: 1.812" Diameter
<b>BALL SIZE</b>	C Size (1.5")
<b>MATERIALS</b>	Steel Marine-grade aluminum High strength composite
<b>PACKAGING TYPE</b>	Poly Bag
<b>OUTPUT VOLTAGE</b>	5-9VDC*
<b>INPUT CONNECTOR</b>	Female USB Type-C
<b>INPUT CABLE LENGTH</b>	1.2 Meters including 2 Pole Flat Marine Connector
<b>OUTPUT CABLE LENGTH</b>	150mm

SPECIFICATIONS	
OPERATING TEMPERATURE	-20°C to +70°C
STORAGE TEMPERATURE	-40°C to +85°C
REGULATORY	Over Voltage Protection Short Circuit Protection Reverse Polarity Protection RoHS Compliance WEEE Compliance SAE J-1113-5 Load Dump (Transient Voltage) Moisture Resistant
CERTIFICATIONS	CE Certification E-Mark Certification RCM Certification FCC Certification UL 62368-1 Certificaton
WARRANTY	3 year warranty
WEIGHT	3.29 lb